

US 360

V3 KNX - in-ceiling installation

EAN 4007841 079628

Article number 079628



ultrasonic sensor
360°



max. Ø 6 m
presence



KNX 4 channel



IP20



ideal 2,5 - 3,5 m



indoor sensor



iQ-mode



Teach mode



energy saving

5 years

manufacturer's
warranty
steinel-professional.de/garantie

Function description

Detects without obstructions. 360° ultrasonic presence detector US 360 KNX, ideal for offices, conference rooms, store rooms and class rooms. 36 sq.m. presence detection zone, immune to obstacles, envelops objects as opposed to penetrating them, detection regardless of temperature, electronically adjustable reach, with digital BUS interface for controlling 4 lighting channels and HVAC.

US 360

V3 KNX - in-ceiling installation

EAN 4007841 079628

Article number 079628



Technical specifications

Type	Presence detector
Dimensions (L x W x H)	105 x 120 x 120 mm
Mains power supply	24 – 29 V
Sensor Technology	Ultrasonic
Application, place	Indoors
Installation site	ceiling
Installation	In-ceiling installation
Mounting height	2,50 – 2,8 m
Reach, radial	Ø 10 m (79 m ²)
Reach, tangential	Ø 10 m (79 m ²)
Reach, presence	Ø 6 m (28 m ²)
Ultrasonic technology	40 kHz
Detection angle	360 °
Angle of aperture	180 °
Optimum mounting height	3,5 m
Mechanical scalability	No
Sneak-by guard	Yes
Capability of masking out individual segments	No
Electronic scalability	Yes
Twilight setting TEACH	Yes

Twilight setting	10 – 1000 lx
Time setting	0 s – 1092 Min.
Constant-lighting control	Yes
Basic light level function	Yes
Basic light level function time	1-30 min, all night
KNX functions	Photo-cell controller, Basic light level function, Light level, HVAC output, Constant-lighting control, Light output 4x, Presence output, Day / night function, Logic gate
With bus coupling	Yes
Settings via	ETS software, Remote control, Bus, Smart Remote
Interconnection	Yes
Type of interconnection	Master/master, Master/slave
IP-rating	IP20
Material	Plastic
Ambient temperature	-20 – 55 °C
Application, room	classroom, one-person office, open-plan office, conference room / meeting room, duty room, recreation room, function room / ancillary room, stairwell, WC / washroom, Indoors
Colour	white
Colour, RAL	9010
Manufacturer's Warranty	5 years
Version	KNX - in-ceiling installation
PU1, EAN	4007841079628
Technology, sensors	High frequency, Photo-cell controller

Accessories


EAN 4007841 003036	Control PRO guard cage
EAN 4007841 009151	Remote control Smart Remote
EAN 4007841 593018	Service remote control RC6 KNX
EAN 4007841 592912	User remote control RC7 KNX

US 360

V3 KNX - in-ceiling installation
EAN 4007841 079628
Article number 079628



Detection Zone



Mögliche Montagehöhe: 2,50 m – 2,80 m
Orange: Präsenz und tangential
Schwarz: radial

Dimension Drawing

