

2N

2N Clip 2wire-IP

The power of IP via 2 wires

Bring a meaningful upgrade to the retrofit market, not just a routine replacement. The 4" display IP indoor station delivers high-quality video and connects directly to existing legacy cabling.

Enhance the resident experience

Combine 2N Clip 2wire-IP with other parts of 2N's solutions and offer features like convenient mobile access or our handy intercom to mobile phone calls feature.

Advantages of a pure IP product

Even when connected to legacy cabling, this product delivers all the advantages of an IP-based system, including the level of reliability you expect from 2N OS-based products.

Remote management

9 times out of 10 you can handle your customer requests from your home or office, significantly reducing travel time and costs.

Upgrade to IP video

High-definition IP video enhances building security by providing clear visual identification of visitors, and unlike analogue systems, it's far less prone to signal interference.

Fast track installation

Experience the 2N installation that's quicker than ever before. Just drill in two screws, connect the legacy 2wire cables, and clip the 2N Clip to the wall!


Easy to operate

There are only three clearly visible buttons, making the device easy to use for everyone, especially older people. Add a tactile sticker to make it even easier for residents with visual impairments to use.

Variants



2N Clip 2wire-IP
9138521



**2N Clip 2wire-IP,
Induction loop**
9138522



2N Clip 2wire-IP Switch
9138001




**Power supply for the
2N Clip 2wire-IP Switch**
1120302



2N Clip Desk Stand
9138002

Connection scheme



2N Clip 2wire-IP Technical Parameters

| Power supply | |
|------------------------------|---|
| Type | 2wire-IP powered, 48 V DC, 200 mA |
| User interface | |
| Controls | 3 capacitive buttons |
| Operation | press and hold the RESET button to restore factory settings |
| Audio | |
| Microphone | integrated |
| Speaker | integrated, 2W/8 Ω |
| Integrated induction loop | optional |
| Codecs | G.711a/u, G.722, G.729, L16/16 kHz |
| Video | |
| Display | 4.3" colour display |
| Resolution | 480×272 pixels |
| Codecs | H.264 |
| Interface | |
| Two wire | 2wire-IP |
| Recommended cabling | 1 pair of Cat3 or higher, 24AWG |
| Important note | always verify condition of the legacy cabling before use |
| Doorbell input | |
| Input type | switching contact (button/relay) |
| Contact type | normally open (NO) |
| Contact parameters | 12V/20mA, DC |
| Mechanical properties | |
| Dimensions | 124 (W) × 150 (H) × 28 (D) mm |
| Weight | 235 g |
| Operating temperature | 0 to 50°C |
| Storage temperature | -20 to 70°C |
| Relative operating humidity | 10 to 90 % (non-condensing) |
| Recommended altitude | 0 to 2000 m |
| Warranty | |
| 5-year warranty. See: | https://www.2n.com/en_GB/support/warranty-and-repairs |

2N Clip 2wire-IP Switch Technical Parameters

| Power supply | |
|------------------------------|---|
| Type | external source, 48V DC, 1.92A |
| Interface | |
| Two wire | 6x 2wire-IP (max. 10Mbps data) powered for connection of 2N Clip 2wire-IP |
| | 2x 2wire-IP (max. 100Mbps data) passive for connection of another 2N Clip 2wire-IP Switch |
| LAN | 2x10/100BaseT, RJ-45 |
| PoE | one LAN port providing 802.3af Class 0 (up to 25W) |
| USB port | unused (for service purposes only) |
| Recommended cabling | Cat5e or higher, 24AWG |
| Important note | always verify condition of the legacy cabling before use |
| Mechanical properties | |
| Dimensions | 155 (W) × 88 (H) × 59 (D) mm |
| Weight | 313 g |
| Operating temperature | -10 to 50°C |
| Storage temperature | -20 to 70°C |
| Relative operating humidity | 10 to 90 % (non-condensing) |
| IP rating | IP20 |
| Recommended altitude | 0 to 2000 m |
| Mounting | DIN-rail mountable into the electrical switchboard |
| Warranty | |

5-year warranty. See:
https://www.2n.com/en_GB/support/warranty-and-repairs