

LUXOMAT® PD4-DIM-KNX/EIB-C-SM/FC/FM



For KNX/EIB with
narrow detection area




SM



FC



FM




■ TECHNICAL DATA

	24 VDC from KNX/EIB-BUS network
	Ø 360°
	across Ø 40.00 m towards Ø 20.00 m
	IP20 / Class II / C
	SM Ø 98 x H 65 mm FC Ø 97 x H 103 mm FM Ø 97 x H 84 mm
	-25°C to +55°C
	Housing UV- and shock-resistant Polycarbonate
	For integration in KNX/EIB-BUS systems

► Before programming, please note the device and software version.

■ PRODUCT INFORMATION

- Occupancy detector LUXOMAT® PD4-DIM-KNX/EIB-C for building services engineering, which is based on KNX/EIB-BUS-network (European Installation Bus).
- **Typical applications:**
monitoring of long corridors
- **Dimming version:**
 - With integrated bus coupler! Connection via WAGO standard bus connector
 - When using the BEG_DIM_HKL_V4.0 application program, four different operating modes are available:
 - Standard mode (semi-automatic or fully automatic mode (**switching**))
 - Semi-automatic or fully automatic mode with **constant light control (dimming)**
 - Slave mode
 - **NEW:** Permanent dimmer (light control that is not dependent on presence)
- Specification of three target values: Two target values are regulated (specified in Lux) and one target value is a fixed setpoint (specified in %)
- Target values can be changed using a communication object.
- Soft start to slowly switch on the lighting to the target value
- **NEW:** Reflection factor for improved adjustment to the ambient conditions
- **NEW:** HVAC channels (switch channels) can now be switched using a pushbutton



1 ■ Walking towards
2 ■ Walking across

■ ACCESSORY (OPTIONAL)



Description	Colour	Part number
PD4-DIM-KNX/EIB-C-SM	white	92461
PD4-DIM-KNX/EIB-C-FC	white	92456
PD4-DIM-KNX/EIB-C-FM	white	92459
Accessory (optional)		
Wire basket BSK	white	92199
Socket IP54 for PD4-SM	white	92161
Wall bracket for PD4-C-SM	white	92441