

instabus KNX/EIB Control unit 3gang 1-10V 16A manual status RMD light grey (01.11.2005)



Order no. 7531 30 05

Packing unit 1

Operating voltage over bus 21 - 32 V=

Control current per channel 100 mA

Max. switching current at 230 V~

Switching current 16 A

Capacitive load 1000 W, 140 μ F

Insta EVG -

EVG TC 1-10 V single flame 15

EVG TC 1-10 V double flame 12

Osram electronic ballasts (EVG) -

QT-FH 1x28W 17 units

QT-FH 2x28W 17 units

QT-FQ 2x80W 11 units

Operating temperature -5 - +45 °C

Input cable length max. 500 m with 0,5 mm²

RMD 4 modules

Dimensions (W x H x D) 72 x 90 x 65 mm

Assembling height as from DIN rail 58 mm

Interface DIN EN 60928

- for switching and controlling electr. ballasts (EVGs) and Tronic transformers with 1-10 V interface
- suitable to switch different external conductors
- with potential-free normally-open contacts
- basic brightness programmable
- with manual selection switch per channel for on/off and status indication
- manual operation also possible without bus e.g. on building site
- behaviour in the event of bus voltage failure programmable
- with programming button
- with red programming LED and red status LED
- bus connection via connecting terminal
- with screw terminals