

instabus KNX/EIB Switch actuator 4gang 16A NO manual status RMD light grey (01.11.2005)



Order no. 7531 40 07 #
Packing unit 1

Operating voltage over bus 21 - 32 V=
Max. switching capacity for 230 V~
Incandescent lamps and HV halogen lamps 2500 W
Conventional transformers 500 VA
Electronic transformers 1300 W
Fluorescent lamps -
uncompensated 2500 W
parallel compensated 1300 W / 140 μ F
Duo circuit at cos phi 1 = 2 x 2500 W
Osram electronic ballasts (EVG) -
QTP 4x18W 17 units
QTP 2x36W 17 units
QTP 1x58W 17 units
QTP 2x58W 11 units
QT-FH 1x28W 17 units
QT-FH 2x28W 17 units
QT-FQ 2x80W 11 units
Operating temperature -5 - +45 °C
RMD 4 modules
Dimensions (W x H x D) 72 x 90 x 65 mm
Assembling height as from DIN rail 58 mm

- also for simplified programming/commissioning with ETS3 starter
- for switching e.g. 4 independent loads
- suitable to switch different external conductors
- with potential-free normally-open contacts as well as normally-closed contact can be parameterised
- with manual selection switch per channel for on/off and status indication
- manual operation also possible without bus e.g. on building site
- with programming button and red programming LED
- bus connection via connecting terminal
- with screw terminals