

**instabus KNX/EIB Radio receiver
surface-mounted
(01.11.2005)
white**



Order no. 7563 00 04

Packing unit 1

Operating voltage over bus 21 - 32 V=

Function channels 50

Teachable radio transmitters (buttons) 100

Radio signal reception frequency 433,42 MHz

Operating temperature -5 - +45 °C

Dimensions (W x H x D) 110 x 94 x 38 mm

for order-no.

Best.-Nr. 0124 10

Best.-Nr. 0174 01 09

Best.-Nr. 2721 00 02

Best.-Nr. 2721 00 69

Best.-Nr. 2721 02

Best.-Nr. 2721 09

Best.-Nr. 2721 14 04

Best.-Nr. 2721 16 06

Best.-Nr. 2721 19 09

Best.-Nr. 2721 70 04

Best.-Nr. 2721 70 09

Best.-Nr. 2721 90 04

Best.-Nr. 2721 90 11

Best.-Nr. 2722 00 02

Best.-Nr. 2722 00 69

Best.-Nr. 2722 02

Best.-Nr. 2722 09

Best.-Nr. 2722 14 04

Best.-Nr. 2722 16 06

Best.-Nr. 2722 19 09

Best.-Nr. 2722 70 04

Best.-Nr. 2722 70 09

Best.-Nr. 2722 90 04

Best.-Nr. 2722 90 11

Best.-Nr. 2723 10 06

Best.-Nr. 2723 10 09

Best.-Nr. 2723 70 04
Best.-Nr. 2723 70 09
Best.-Nr. 2724 00 02
Best.-Nr. 2724 00 69
Best.-Nr. 2724 02
Best.-Nr. 2724 09
Best.-Nr. 2724 14 04
Best.-Nr. 2724 16 06
Best.-Nr. 2724 19 09
Best.-Nr. 2724 90 04
Best.-Nr. 2724 90 11
Best.-Nr. 2764
Best.-Nr. 2766
Best.-Nr. 2769
Best.-Nr. 9420 00 02
Best.-Nr. 9420 00 69
Best.-Nr. 9420 02
Best.-Nr. 9420 09
Best.-Nr. 9420 14 04
Best.-Nr. 9420 16 06
Best.-Nr. 9420 19 09
Best.-Nr. 9420 70 02
Best.-Nr. 9420 70 09
Best.-Nr. 9420 90 04
Best.-Nr. 9420 90 11
Best.-Nr. 9430 01 00

- processing the radio signals of hand-held, wall-mounted radio transmitters and radio controllers
- for switch, push-button, dimmer and shutter functions
- dimming / position value transmitter 1 byte
- extension unit for light scene push-button
- with 2-digit, 7-segment function channel display
- with programming button and function channel selection button
- with green operation LED and red programming LED
- with fitting material
- bus connection via connecting terminal
- with screw terminals

The surface-mounted radio receiver converts signals of taught-in radio bus transmitters into instabus KNX/EIB telegrams.

For teach-in of radio transmitters a 9 V block battery is required, e.g. order no. 9209.