

instabus KNX/EIB Bus coupling unit flush-mounted version 2



Order no. 7504 00 02

Packing unit 1

Operating voltage over bus 21 - 32 V=

Operating temperature -5 - +45 °C

Insertion depth 15 mm

for order-no.

Best.-Nr. 7566 02 12

Best.-Nr. 7566 02 19

Best.-Nr. 7566 02 42

Best.-Nr. 7566 02 43

Best.-Nr. 7566 02 44

Best.-Nr. 7566 02 49

Best.-Nr. 7566 02 83

Best.-Nr. 7566 02 85

Best.-Nr. 7566 02 89

Best.-Nr. 7506 01 89

Best.-Nr. 7506 01 85

Best.-Nr. 7506 01 83

Best.-Nr. 7506 01 12

Best.-Nr. 7506 01 19

Best.-Nr. 7506 01 42

Best.-Nr. 7506 01 43

Best.-Nr. 7506 01 44

Best.-Nr. 7506 01 49

Best.-Nr. 7506 01 65

Best.-Nr. 7506 01 66

Best.-Nr. 7506 01 69

Best.-Nr. 7566 02 52

Best.-Nr. 7566 02 59

Protective cover see accessories order no.

Best.-Nr. 7500 00 07

- as interface between data interface FTP 1.2 and IR gateway with bus line
- with programming button and red programming LED
- bus connection via connecting terminal
- without spreader claws

For special applications with data interface FTP 1.2 order no. 7506 01 .. and IR gateway order no. 7566 02 ..!!Not suitable for other user modules!