

instabus KNX/EIB Bus coupling unit plus flush-mounted (01.11.2005)



Order no. 7504 00 03

Packing unit 1

Operating voltage over bus 21 - 32 V=

Operating temperature -5 - +45 °C

Insertion depth 20 mm

for order-no.

Best.-Nr. 7566 01 12

Best.-Nr. 7566 01 19

Best.-Nr. 7566 01 83

Best.-Nr. 7566 01 85

Best.-Nr. 7566 01 89

Best.-Nr. 7566 01 42

Best.-Nr. 7566 01 43

Best.-Nr. 7566 01 44

Best.-Nr. 7566 01 49

Best.-Nr. 7566 35 99

Best.-Nr. 7566 35 93

Best.-Nr. 7566 35 91

Best.-Nr. 7566 36 91

Best.-Nr. 7566 36 93

Best.-Nr. 7566 36 99

Best.-Nr. 7566 45 91

Best.-Nr. 7566 45 93

Best.-Nr. 7566 01 52

Best.-Nr. 7566 01 59

Best.-Nr. 7566 45 99

Best.-Nr. 7566 46 91

Best.-Nr. 7566 46 93

Best.-Nr. 7566 46 99

Best.-Nr. 7566 55 91

Best.-Nr. 7566 55 93

Best.-Nr. 7566 55 99

Best.-Nr. 7566 56 91

Best.-Nr. 7566 56 93

Best.-Nr. 7566 56 99

Protective cover see accessories order no.

Best.-Nr. 7500 00 07

- for B.IQ push-buttons with room thermostat and display or Bluetooth gateways
- with programming button and red programming LED
- bus connection via connecting terminal
- without spreader claws