



Blind actuator, 6 A 4gang

Functions at a glance

- 230 V~, 50 Hz, 4 x 6 A
- For controlling of 4 independent blind groups.
- Rated voltage: 230 V~, +10 % / -15 %
- Rated frequency: 50 Hz / 60 Hz
- Outputs: 4 Change-over switch
- Laststart: AC1/AC3
- Rated current: 6 A
- Protection class (device): IP 20
- Temperature range (device): -5 °C - 45 °C
- Storage temperature range: -25 °C - 55 °C
- Transport temperature range: -25 °C - 70 °C
- Dimensions: (L x W x D): 90 mm x 72 mm x 64 mm
- Module width: 4
- Mounting depth: 68 mm
- ETS programming only from ETS 3f.
- Also usable as a binary output (one channel per output).

Order details

Article No.:	6196/40-102
Order No.:	2CKA006151A0217
EAN:	4011395132388
Preisgruppe:	44
Preis:	277,00 EUR plus VAT
Info sheet:	» Download PDF

Downloads

Instruction manual

» INT

Technical manual

» Technical manual

Certificates

» EU-declaration of conformity

Software

- » ETS4/ETS5 application , V 1.4, 24.07.2017
- » ETS3 application , V 1.4, 24.07.2017
- » Additional software :i-bus tool , V 1.9.37.0, 25.02.2019