



Outdoor video station, 1gang

Functions at a glance

- Video camera with automatic day/night switchover and infrared LEDs to illuminate the night shots.
- Communication unit and key module are backlit.
- Stamped labelling foil is enclosed.
- Mounting tool is enclosed.
- For flush-mounted installation with 41383F-H-03 / 41383F-B-03.
- For surface-mounted installation with 41383S-B-03 / 41383S-H-03.
- Vertical/horizontal detection angle: 86°/67°
- Setting angle horizontal/vertical: +/-15°, mechanically adjustable
- Consumer units: 8
- Protection class (device): IP 44
- Temperature range (device): -25 °C - 55 °C
- Dimensions: (L x W x D): 277 mm x 135 mm x 43 mm
- Not suitable for use with the camera interface (83327) nor camera module 180° (83503).
- Additional information about commissioning and operation is contained in the system manual and the online operating manual of the current Online-Catalogue.
- Front plate made of 3 mm stainless steel, surface is brushed

Order details

Article No.:	83121/1-660
Order No.:	2CKA008300A0022
EAN:	4011395155172
Customs tariff number:	85177000
Preisgruppe:	23
Preis:	1.333,00 EUR plus VAT
Info sheet:	» Download PDF

Downloads

Instruction manual

- » [Operating Instructions](#)
- » [Product manual](#)

Certificates

- » [EU-declaration of conformity](#)
- » [ROHS product declaration](#)

Films on application

- » [Outdoor station: installation](#)
- » [Labelling strip: Mounting](#)
- » [End Strip: Dismounting](#)
- » [ABB-Welcome - Comfort \(mp4\)](#)
- » [ABB-Welcome - Comfort \(wmv\)](#)
- » [ABB-Welcome - Safety \(mp4\)](#)
- » [ABB-Welcome - Safety \(wmv\)](#)