

IP-Gateway



Functions at a glance

- Allows the integration of tablet or smartphone with installed Welcome app as mobile indoor load for audio and video communication.
- Makes possible the use of the Busch-ComfortTouch® as indoor door communication.
- For integration into the myBUSCH-JAEGER portal.
- Configuration interface for telephone gateway and access control module.
- Ethernet connection (RJ 45).
- Consumer units: 11
- Protection class (device): IP 20
- Temperature range (device): -5 °C - 45 °C
- Dimensions: (L x W x D): 90 mm x 180 mm x 65 mm
- Module width: 10
- Additional information about commissioning and operation is contained in the system manual and the online operating manual of the current Online-Catalogue.

Order details

Article No.:	83342
Order No.:	2CKA008300A0374
EAN:	4011395197554
Customs tariff number:	85177000
Preisgruppe:	23
Preis:	336,00 EUR plus VAT
Info sheet:	» Download PDF

Downloads

Instruction manual

- » [Product manual](#)
- » [myABB-LivingSpace](#)
- » [Terms of a licence](#)
- » [Operating Instructions](#)
- » [Film Software Update 3.52](#)
- » [PDF Software Update 3.52](#)
- » [FAQ - IP-Gateway Update](#)

Technical manual

- » [System manual](#)

Certificates

- » [ROHS product declaration](#)

Software

- » [Firmware , V 3.52, 01.10.2018](#)
- » [Firmware :For the IP gateway predecessor version 83341, please follow this link. , V 1.22](#)
- » [IP-Gateway 83441 - Link](#)

Wiring diagram

