

Telephone gateway



Functions at a glance

- For connecting an ABB-Welcome system with the analog inputs of a private branch exchange (PBX).
- Permits the use of a telephone (e.g., DECT, ISDN, mobile telephone) as indoor door communication station.
- Taking door calls, opening the door and switching the light via the telephone keypad (DTMF).
- Switching between the freely-programmable target numbers via the telephone keypad (DTMF).
- PIN protection for all configuration settings.
- For ABB-Welcome systems with up to 99 apartments.
- Programming via the telephone keypad (DTMF) or via web browser (requires IP gateway 83342-5..).
- 2 screw-type terminals for the analogue a/b connection of the telephone system.
- Consumer units: 1
- Protection class (device): IP 20
- Temperature range (device): -5 °C - 45 °C
- Dimensions: (L x W x D): 90 mm x 72 mm x 65 mm
- Module width: 4
- Additional information about commissioning and operation is contained in the system manual and the online operating manual of the current Online-Catalogue.

Order details

Article No.:	83350
Order No.:	2CKA008300A0373
EAN:	4011395197509
Customs tariff number:	85177000
Preisgruppe:	23
Preis:	258,00 EUR plus VAT
Info sheet:	» Download PDF

Downloads

Instruction manual

- » [Operating Instructions](#)
- » [Product manual](#)

Technical manual

- » [System manual](#)

Certificates

- » [EU-declaration of conformity](#)
- » [ROHS product declaration](#)

Wiring diagram

