

DIVUSHOME WALLMOUNT

MHxx

WALL MOUNT BOX

Types	in wall mount box	in mortarless mount kit
for DH10 – 10,4“	MH10	MH10T
for DH15 – 15“	MH15	MH15T
Technical Data		
Type of design	compact, stable and flat wall mount box	compact mounting kit for mortarless constructions
Dimensions (mm)		
Cut-Out dimensions 10,4”	MH10 313x258x80	MH10T 313x258
Cut-Out dimensions 15”	MH15 399x336x90	MH15T 399x336
Weight	ca. 4kg	ca. 2kg
Mechanical Characteristics		
Wall mount box	powder coated metal with cover for clean installation	steel plate with pattern for easy installation
Cable access	2xtop, 2xbottom, 2xleft, 2xright	on the back
		
Grounding	in addition to the DIVUSHOME even the MHxx needs to be professionally grounded	
Montage / Installation instructions / Installazione		
 Die Unterputzdose und das Trockenbaukit MHxx können in einem Ausschnitt in der Wand oder in einem bis zu 1,5 cm dünnen Möbelstück, sowie in einem Trockenbau befestigt werden. Der Ausschnitt muss den in den technischen Details spezifizierten Maßen entsprechen und beim Wandeinbau mindestens 9 cm tief sein. Im Wandausschnitt wird die Unterputzdose eingemauert, während sie im Möbelstück angeschraubt werden kann. Es ist wichtig, dass die vordere Kante der MHxx plan und waagrecht zur Oberfläche der Wand oder des Möbelstückes ist.  The wall mount box an the mounting kit may be installed in a cut out in the wall, in a wooden structure thick at least 1,5 cm or in a dry mortarless construction. The cut out has to respect the sizes specified in the technical data and has to be at least 9 cm deep. In the wall cut out, the box can become build in while it can be screwed on in a piece of furniture. It is important that the fore edge of the MHxx is flat and horizontally to the surface of the wall or the piece of furniture.  Il box di installazione ed il kit di montaggio possono essere incassati o montati a muro, in un pannello di legno di spessore minimo di 1,5 cm o in un muro di cartongesso. Le dimensioni di taglio sono quelle espresse nella tabella tecnica, la profondità minima è di 9 cm. Verificare a mezzo di una livella che il MHxx venga fissato in posizione orizzontale ed in modo complanare al muro o alla superficie di montaggio.		

