

PD-ATMO 360i/8 A KNX

Item number	GTIN
EP10427206	4015120427206



Technical data

GENERAL

Device category	Ceiling-mounted presence detector
Included in delivery	Includes lens mask
User interface	IR remote control, ETS-Software
Remote controllable	✓
Conformity	CE, EAC, RoHS, WEEE
Warranty	5 years

ATTACHMENT

Installation type	Recessed mounting / device box Ø 68 mm
Installation position	Ceiling
Installation dimension	Installation depth: 24 mm, Ø 60 mm
Type of connection	Push terminal
Connectable wire cross section	0.60 – 0.80 mm ²
Number of contacts	4

HOUSING

Dimensions	Height/Depth 38 mm, Ø 108 mm
Weight	162 g
Material	UV-stabilised polycarbonate
Protection type	IP20
Permissible ambient temperature	5 °C...+35 °C
Relative humidity	5 - 93 %, non-condensing
Colour	white, similar to RAL 9010

ELECTRICAL VERSION

Control system	KNX
Protection class	III
Nominal voltage	29 - 31 V DC

Product description

- KNX recessed ceiling-mounted presence detector with 360° field of detection
- Range of up to 8 m in the diameter at a recommended installation height of 3 m
- In-built acoustic sensor perfect for use in areas with a complex layout
- Additional measurement of the ambient temperature and relative humidity
- For use in KNX (EIB), TP (twisted pair) bus system in conjunction with other KNX components
- Parameter and function settings via ETS (Engineering Tool Software)

Offers special product features like:

- Sensor devices: Humidity, temperature, acoustics, light, presence
- Presence and daylight dependent constant light control
- KNX functions: Alarm via object, twilight switch (one object), brightness detection via object, light-dependent motion detection, scene telegram via object, night-light feature (seven colours available)

Power consumption	0.2 W
Power consumption	6 mA
Stand-by consumption	< 0.3 W

SENSORS

Detection angle	360°
Detection range diagonally	Ø 8 m
Detection range head-on	Ø 6 m
Detection range presence	Ø 4 m
Field of detection	up to 50 m ²
Recommended installation height	3 m
Max. mounting height	5 m
Light measurement	mixed light
Level of brightness	5–2000 lx

CHANNELS (LIGHTING / HVAC)

Number of light channels	2
Number of HVAC-channels	1
Push button input lighting	2
Push button input HVAC	✓
Slave input	✓
Mode	Semi-automatic, Fully automatic
Switching delay from "dark to light"	300 s
Switching delay from "light to dark"	30 s
Constant light control	✓
Sensitivity configurable	✓
KNX input	manual light control, block objects, reset, slave
KNX output	presence, status, light value, HVAC

PD-ATMO 360i/8 A KNX

Item number	GTIN	
EP10427206	4015120427206	
KNX functions	Presence simulation, Constant lighting control, Manual override, Master- / slave-toiminto, Night-light feature, Sensitivity configurable, Sends a telegram at regular intervals	
Channel	C1 Lighting	Offset setting
Function	Switching, Regulate	c2 offset from c1 (-100 % to +100 %)
Switch contact	Bus system	Switch contact
Push button input	—	Push button input
Impulse mode	—	Impulse mode
Switch-off delay time	30 s...720 min (adjustable in steps)	Switch-off delay time
Orientation light	disabled/10 - 50 %, 2 values can be selected	Orientation light
Switch-off delay time, orientation light	60 s...250 min	Switch-off delay time, orientation light
Channel	C2 Lighting	Channel
Function	Switching, Regulate	C3 HVAC
		Function
		Switch contact
		Push button input
		Switch-on delay
		Impulse mode
		Switch-off delay time

Factory settings

GENERAL			
Sensitivity	90 %	Operating mode	fully automatic
Orientation light ON	—	Level of brightness/switching threshold	500 lx
Orientation light, depending on brightness	✓	Switch-off delay time	5 min
Switching threshold for orientation light	500 lx	Luminous efficiency of orientation light	10 %
Deviation (%)	0 %	Channel	C2 HVAC
Luminous efficiency switch-on value	60 %	Operating mode	fully automatic
CHANNELS (LIGHTING / HVAC)		Level of brightness/switching threshold	500 lx
Channel	C1 Lighting	Switch-off delay time	60 min
		Luminous efficiency of orientation light	25 %

Accessories

Product designation	Item number	Product description	GTIN
Mounting			
COMPACT MOUNTING BOX IP20 SM WH	EP10425370	Surface-mounted box for COMPACT series, IP20, white	4015120425370
COMPACT MOUNTING BOX IP54 SM WH	EP10425905	Surface-mounted box for COMPACT series, IP54, white	4015120425905
MOUNTING SET IP20 FM 62 WH	EP10425929	Recessed ceiling mounting set includes installation bracket and dust-protected box, 62 mm	4015120425929
Protection			
BASKET GUARD ROUND LARGE	EM10425608	Basket guard for presence and motion detectors and smoke detectors, Ø 180 mm, height 90 mm,	4015120425608
BASKET GUARD ROUND SMALL	EM10425615	Basket guard for presence and motion detectors and smoke detectors, Ø 165 mm, height 70 mm,	4015120425615
Remote control			
REMOTE CONTROL PDi/USER	EM10425547	IR remote control for end users of presence detectors	4015120425547
TELESCOPE MAGNET	EC10430022	Telescope magnet	4015120430022

PD-ATMO 360i/8 A KNX


Item number

GTIN


EP10427206

4015120427206

Dimension drawing



Field of detections



Detection range

Diagonally (A)

 $\emptyset 8\text{ m}$


Frontal (B)

 $\emptyset 6\text{ m}$

Presence area (C)

 $\emptyset 4\text{ m}$

Circuit diagram



Standard operation