

Technical DATA EIB-TAB 32 XX

Technical Data	KNX-Tableau with 32 Buttons / LED KNX-TAB 32 xx	
material (front plate)	anodized aluminum	
material (inscription plate)	anodized aluminum	
amount of inscription plates	4	
dimension front plate H x W x D:	299 x 260 x 3 mm	
dimension concealed-type junction case	279 x 240 x 87 mm	
acoustic signal	2 built-in buzzer	
control objects	32 buttons, front panel mounting	
indicators	32 LED, red/green, integrate in button	
connections	KNX-connection (z. B. KNX-Y-(St)2x2x0,8)	black wire:- KNX red wire: + KNX
Busline consumption:	ca. 22 mA	
auxiliary voltage	no	
weight (without housing)	ca. 1030 g	

Note: From September 2012 new hardware and software!

Technical DATA EIB-TAB 32 XX

Technical Data	KNX-Tableau with 31 Buttons / LED+1 keyswitch KNX-TAB 31/x	
----------------	---	---

material (front plate)	anodized aluminum	
material (inscription plate)	anodized aluminum	
amount of inscription plates	2	
dimension front plate H x W x D:	299 x 260 x 3 mm	
dimension concealed-type junction case H x W x D	279 x 240 x 87 mm	
acoustic signal	2 built-in buzzer	
control objects	31 buttons, front panel mounting	
	1 keyswitch	
indicators	31 LED, red/green, integrate in buttons	
connections	KNX-connection (z. B. KNX-Y-(St)2x2x0,8)	black wire:- KNX
		red wire: + KNX
Busline consumption:	ca. 22 mA	
auxiliary voltage	no	
weight (without housing)	ca. 1030 g	

Note: From September 2012 new hardware and software!

Technical DATA EIB-TAB 32 XX

Specification of the Aluminum Box for on Wall mounting	KNX-Tableau with 32 Buttons / LED Aluminum Box for on Wall mounting KNX-TAB 32 APAL	
material	aluminum	
depth of the box's walls	2 mm	
dimension (TAB 32) H x W x D	318 x 280 x 52 mm	
weight TAB 32 (incl. Gaskets and cable mounts M16x1,5)	ca. 1200 g	
color	white aluminum RAL 9006, structure matt painted	
attachment	4 wells 4mm at the backside	
attachment of the front plate	countersunk Allen screw M3	
cable entry	1x cable mounts(nickel plated brass), IP68, M16x1,5	
gaskets between the aluminum box and the front plate	cellular rubber, HY/CR middle 2 mm, self-stick with H42 mounting aid	
Specification of the Buttons	For all Buttons	
material (top)	stainless steel	
mechanical safety	unbreakable	
contact material	silver	
protection (front)	IP 40	
protection (room of contact)	IP 65	
deflection	0,4 mm	
mounting	on the front plate with gaskets	

Status: 11. April 2013

Subject to technical changes!

The GePro- Tableaus enrolled in the Industrial Design of the German Patent and Trademark Office.



GePro- Gesellschaft für Prozesstechnik mbH
Heinrich-Heine-Ring 78
18435 Stralsund

Fon: +49 3831 – 39 00 55
Fax: +49 3831 – 39 00 24
Email: info@eib-tab.de

www.eib-tab.de
<http://knxtab.de/>

