

Technical data KNX-push-button 4

KNX-push-button 4		Basic element with integrated bus coupling unit	
dimension support ring with mounting holes for installation in commercial '68 boxes	ca. 70 mm		
Installation depth in box	ca. 20 mm		
control objects	4 push-button		
indicators	4 RGB LED (Red / Green / Blue / White / Yellow / Cyan / Violet) integrated in push-button brightness adjustable in 7 steps (ETS parameter)		
connections	KNX-connection (e.g. KNX-Y-(St)2x2x0,8)	black wire: - KNX	
		red wire: + KNX	
auxiliary supply	no		
weight	ca. 60 g		
KNX-programming	with ETS 4.1 or higher no plugin no additional software		
Plaster compensation ring		PAR	
dimension support ring with mounting holes for installation in commercial '68 boxes	ca. 70mm		
compensation height	0,5 mm		
mounting	mounting under basic element concealed – or cavity wall socket		

Technical data KNX-push-button 4

cover onefold for basic element KNX-push-button 4		Backlight-KNX	
dimensions H x W x D	75 x 75 x 6 mm		
material	acrylic glass		
weight cover	ca. 30 g		
mounting	screwless with magnetic holder on basic element		
colors backlight KNX	silver		
	red		
	aqua-grey		
	lemon		
	white		
	anthracite		

cover 1-fach for basic element KNX-TASTER 4		Frontlight-KNX	
Dimensions H x W x D	75 x 75 x 6 mm		
material	acrylic glass		
weight cover	ca. 30 g		
mounting	screwless with magnetic holder on basic element		
Colors frontlight KNX	black		

Update: 2014-05-13

Subject to technical changes!

The GePro KNX BUTTONS are filed with the German Patent & Trademark Office.