

Product data sheet

Smart Control 15



Reference number

SC 15.1

Smart Control 15

aspect ratio 16:9

for installation in walls, capacitive touch screen
fanless, without rotating parts

Intended use

- Visualisation and operation of system statuses and information on building automation
- For horizontal installation
- Mounting in flush-mounted recessed box

Product characteristics

- KNX visualisation in combination with Visu Pro Server (ref.-no.: JVP-SERVER-H2, JVP-SENEC-H2)
- KNX visualisation in combination with Smart Visu Server (ref.-no.: SV-SERVER-INT)
- eNet visualisation in combination with eNet server for rail mounting (ref.-no.: ENET-SERVER) with software version 2.2 or higher
- Door call function only in combination with Siedle Smart Gateway SG 650-.. or SG 150-..
- Pre-installed weather page
- Display of up to six IP camera images
- Cleaning function
- Smart Gateway with integrated image storage

Please check Release Notes.

Accessories:

Flush-mounted recessed box ref.-no.: SC 15 EBG

Power supply ref.-no.: NT 2415 REG VDC

Technical data

Screen diagonal:	396 mm / 15.6"
Resolution:	WXGA (1366 x 768), LED backlight display
Frame dimensions (W x H):	510 x 306 mm
Power consumption:	max. 25 W
Power supply:	PoE+ acc. to IEEE 802.3at, with Cat5e/Cat6 cable, length max. 100 m or DC 12 ... 32 V via external power supply (ref.-no. NT 2415 REG VDC, not included)
Operating system:	Android 6
Processor:	Cortex-A53
Main memory:	2 GB
Mass storage:	16 GB Flash (available disc space depends on operating system)
Slot of memory card:	microSD
Loudspeaker:	integrated
Microphone:	integrated

USB ports:	2 x USB 2.0 1 x Mini-USB OTG (accessible from the front)
LAN connections:	1 x 10/100/1000 Mbit/s
Ambient temperature:	0 ... +30 °C
Version:	
39.6 cm – 15.6"	