



Main

Product name	HomeLYnk
Product or component type	Logic controller

Complementary

Communication port protocol	IP (Internet Protocol) KNX Modbus BACnet
[Us] rated supply voltage	24 V DC
Power consumption	2 W
LED indicator	Green LED (CPU load) Green/Red LED (KNX powered/reset)
Physical interface	1 x RJ45 1 x RS485 1 x RS232 1 x TP-UART2
Port Ethernet	10BASE-T/100BASE-TX
Integrated connection type	1 x USB 2.0 port
Control type	RESET push-button
Connections - terminals	KNX bus : bus terminal, 2 x 0.8 mm ² Power supply : clamp terminal, 1.5 mm ² Serial : clamp terminal, 1.5 mm ²
Mounting support	DIN rail
Height	90 mm
Width	52 mm
Depth	58 mm

Environment

Ambient air temperature for operation	-5...45 °C
Operating altitude	<= 2000 m
Relative humidity	<= 93 %

IP degree of protection	IP20
Directives	2002/96/EC - WEEE directive
Standards	IEC 60950-1

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1426 - Schneider Electric declaration of conformity  Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Available