

HF 360-2

V3.2 KNX - Surface wiring

EAN 4007841 064860

Article number 064860



high frequency
sensor 360°



max. Ø 12 m



KNX



IP20



ideal 2,5 - 3,5 m



10 - 10000 lux



10 sec - 1092 min



temperature



air humidity



iQ

Function description

Smart surveillance professional. The HF 360-2 from the new Control PRO 2 range. Modern look and intelligent 360° HF sensor technology – ideal for stairwells and toilet facilities with cubicles. Conveniently adjusted and interconnected via Bluetooth. Interfaces: COM1, COM2, DALI-2 APC, DALI-2 IPD, KNX, IP and BT IPD (Slave). Mounting height up to 3.5 m. Reach: 12 m.

HF 360-2

V3.2 KNX - Surface wiring
EAN 4007841 064860
Article number 064860



Technical specifications

Type	Presence detector
Dimensions (L x W x H)	57 x 123 x 123 mm
Mains power supply	30 V
Power supply, detail	KNX bus
Sensor Technology	High frequency
Application, place	Indoors
Installation site	ceiling
Installation	Surface wiring
Mounting height	2,50 – 4,00 m
Reach, radial	Ø 12 m (113 m ²)
Reach, tangential	Ø 12 m (113 m ²)
Reach, detail	1 or 2 detection directions can be masked out by stickers for adjustment to the room situation.
HF-system	5,8 GHz
Detection angle	360 °
Angle of aperture	140 °
Optimum mounting height	2,8 m
Mechanical scalability	No
Sneak-by guard	Yes
Capability of masking out individual segments	No
Electronic scalability	Yes
Detection	also through glass, wood and stud walls


Twilight setting TEACH	Yes
Twilight setting	2 – 1000 lx
Time setting	10 s – 1092 Min.
Constant-lighting control	Yes
Basic light level function	Yes
KNX functions	Comfort, Photo-cell controller, Individual pyro evaluation, Basic light level function, Light Level, HVAC output, Constant-lighting control, Light output 4x, Humidity output, Presence output, Day / night function, Dewpoint, Temperature output, Logic gate
With bus coupling	Yes
Settings via	ETS software, Bluetooth, Bus
With remote control	No
Interconnection	Yes
Type of interconnection	Master/master, Master/slave
IP-rating	IP20
Material	Plastic
Ambient temperature	-25 – 50 °C
Application, room	function room / ancillary room, kitchenette, stairwell, WC / washroom, Indoors
Colour	white
Colour, RAL	9003
Manufacturer's Warranty	5 years
Version	KNX - Surface wiring
PU1, EAN	4007841064860

HF 360-2

V3.2 KNX - Surface wiring
EAN 4007841 064860
Article number 064860



Detection Zone



Mögliche Montagehöhe: 2,50 m – 4,00 m
Orange: radial und tangential

Dimension Drawing

