

Dual HF

V3 KNX - in-ceiling installation

EAN 4007841 079505

Article number 079505



high frequency
sensor 360°



max. 20 x 3 m



KNX 4 channel



IP20



ideal 2.5 - 3.5 m



indoor sensor



iQ



Teach



Teach mode



energy saving

5 years

manufacturer's
warranty
steinel-professional.de/garantie

Function description

Twice as vigilant! High-frequency corridor sensor Presence Control PRO Dual HF KNX for indoors, ideal for passageways and long corridors, installation height up to 3.5 m, with digital BUS interface for controlling 4 lighting channels and HVAC, DUAL-HF technology that senses movement in two directions for radial detection up to 20 m, detection regardless of temperature, HF-sensor technology also senses movement through glass, wood and stud walls, switches light 'ON' almost instantly.

Dual HF

V3 KNX - in-ceiling installation

EAN 4007841 079505

Article number 079505



Technical specifications

Type	Presence detector
Dimensions (L x W x H)	112 x 120 x 120 mm
Mains power supply	230 V / 50 – 60 Hz
Sensor Technology	High frequency
Application, place	Indoors
Installation site	ceiling
Installation	In-ceiling installation
Mounting height	2,50 – 3,5 m
Reach, radial	20 x 3 m (60 m ²)
Reach, tangential	20 x 3 m (60 m ²)
HF-system	5,8 GHz
Detection angle	360 °
Angle of aperture	140 °
Optimum mounting height	2,8 m
Mechanical scalability	No
Sneak-by guard	Yes
Capability of masking out individual segments	No
Electronic scalability	Yes
Detection	also through glass, wood and stud walls
Twilight setting TEACH	Yes

Twilight setting	10 – 1000 lx
Time setting	0 s – 1092 Min.
Constant-lighting control	No
Basic light level function	Yes
KNX functions	Photo-cell controller, Basic light level function, Light level, HVAC output, Constant-lighting control, Light output 4x, Presence output, Day / night function, Logic gate
With bus coupling	Yes
Settings via	ETS software, Remote control, Bus, Smart Remote
With remote control	No
Interconnection	Yes
Type of interconnection	Master/master, Master/slave
Material	Plastic
Ambient temperature	-25 – 55 °C
Application, room	corridor / aisle, Indoors
Colour	white
Colour, RAL	9010
Manufacturer's Warranty	5 years
Version	KNX - in-ceiling installation
PU1, EAN	4007841079505
Technology, sensors	High frequency, Light sensor

Accessories


EAN 4007841 593018	Service remote control RC6 KNX
EAN 4007841 003036	Control PRO guard cage
EAN 4007841 592912	User remote control RC7 KNX
EAN 4007841 009151	Remote control Smart Remote

Dual HF


V3 KNX - in-ceiling installation
EAN 4007841 079505
Article number 079505



Detection Zone 1



Detection Zone 2



Mögliche Montagehöhe: 2,50 m – 3,50 m
Orange: radial und tangential

Mögliche Montagehöhe: 2,50 m – 3,50 m
Orange: radial und tangential

Dimension Drawing

