

HF 360

V3 KNX - in-ceiling installation

EAN 4007841 079536

Article number 079536



high frequency
sensor 360°



max. Ø 12 m



KNX 4 channel



IP20



ideal 2,5 - 3,5 m



indoor sensor



iQ-mode



Teach mode



energy saving

5 years

manufacturer's
warranty
steinel-professional.de/garantie

Function description

Doesn't miss a thing. HF-presence detector Presence Control PRO HF 360 KNX for indoors, ideal for WCs with toilet cubicles, changing rooms, stairwells, multi-storey car parks, kitchens, installation height up to 3.5 m, with digital BUS interface for controlling 4 lighting channels and HVAC, 1 – 12 m reach, reach is electronically adjustable and can be limited in two directions, detection regardless of temperature, HF-sensor technology also detects movement through glass, wood and stud walls.

HF 360

V3 KNX - in-ceiling installation

EAN 4007841 079536

Article number 079536



Technical specifications

Type	Presence detector
Dimensions (L x W x H)	94 x 120 x 120 mm
Mains power supply	30 V
Power consumption	0,7 W
Sensor Technology	High frequency
Application, place	Indoors
Installation site	ceiling
Installation	In-ceiling installation
Mounting height	2,50 – 3,5 m
Reach, radial	Ø 12 m (113 m ²)
Reach, tangential	Ø 12 m (113 m ²)
Reach, detail	1 or 2 detection directions can be masked out by stickers for adjustment to the room situation.
HF-system	5,8 GHz
Detection angle	360 °
Angle of aperture	140 °
Optimum mounting height	2,8 m
Mechanical scalability	No
Sneak-by guard	Yes
Capability of masking out individual segments	Yes
Electronic scalability	Yes
Detection	also through glass, wood and stud walls
Twilight setting TEACH	Yes

Twilight setting	10 – 1000 lx
Time setting	0 s – 1092 Min.
Constant-lighting control	Yes
Basic light level function	Yes
Basic light level function time	1-255 min
KNX functions	Photo-cell controller, Basic light level function, Light level, HVAC output, Constant-lighting control, Light output 4x, Presence output, Day / night function, Logic gate
With bus coupling	Yes
Settings via	ETS software, Remote control, Bus, Smart Remote
With remote control	No
Interconnection	Yes
Type of interconnection	Master/master, Master/slave
IP-rating	IP20
Material	Plastic
Ambient temperature	-25 – 55 °C
Application, room	function room / ancillary room, kitchenette, stairwell, WC / washroom, Indoors
Colour	white
Colour, RAL	9010
IDs, certificates	VDE
Manufacturer's Warranty	5 years
Version	KNX - in-ceiling installation
PU1, EAN	4007841079536
Technology, sensors	Photo-cell controller, High frequency

Accessories


EAN 4007841 593018	Service remote control RC6 KNX
EAN 4007841 003036	Control PRO guard cage
EAN 4007841 009151	Remote control Smart Remote
EAN 4007841 592912	User remote control RC7 KNX

HF 360

V3 KNX - in-ceiling installation
EAN 4007841 079536
Article number 079536




Detection Zone 1



Mögliche Montagehöhe: 2,50 m – 3,50 m
Orange: radial und tangential

Detection Zone 2



Mögliche Montagehöhe: 2,50 m – 3,50 m
Orange: radial und tangential

Dimension Drawing

