

Product details

SHUTTER ACTUA.2F GESIS EIB V-0/2W SI SP

gesis EIB V 2-fold sunblind output with positioning has a 1-phase mains supply (3-pole GST18i3) connection. The software allows setting the sunblinds directly to a position of the height and the angle of the lamellae. The flat device is for surface mounting and can be adapted directly to the flat cable. If a flat cable is used the adapters for mains and KNX are separate with a spacer which is added to the special KNX adapter. All electrical connections are pluggable.



Basic information

Article number	83.020.0211.4
EAN	4049088020254
Unit of measure	Piece
Packaging Quantity	1

Classification

Technical Classification	Shutting actuator for bus system
Wieland Product Families	Flat and suitable for the flat cable - gesis EIB V

Ausgänge

Max. number of venetian-blind outputs	2
---------------------------------------	---

General Data

Bus system EIB/KNX	Yes
Bus system LON	No
Bus system radio frequent	No
Bus connection included	Yes
Mounting method	Surface mounted (plaster)
Connection type	Plug-in connection
Degree of protection (IP)	IP20
Colour	Grey
RAL-number (akin)	7035
Modular expandability	No

Feed In

Operating voltage	230 V
Voltage type	AC

Product details

Bus input	KNX TP1
Different phases connectable	No
Additional power supply	No

Output

Max. switching power	2000 W
Voltage of shutter output	230 V
Voltage type of shutter output	AC
Current of shutter output	8 A
Manual control/hand actuation	Yes

Dimensions

Width	254 mm
Height	112 mm
Depth	32 mm
Width in number of modular spacings	