

# Product details

## COMB.ACTUATOR TRI GESIS EIB V-0/2+1W SP

The gesis EIB V 3-fold combined output with 2 x switching and 1 x sunblind output has a 1-phase mains supply (3-pole GST18i3) connection. The flat device is for surface mounting and can be adapted directly to the flat cable. If a flat cable is used the adapters for mains and KNX are separate with a spacer which is added to the special KNX adapter. All electrical connections are pluggable.



### Basic information

Article number	83.020.0212.4
EAN	4015573987784
Unit of measure	Piece
Packaging Quantity	1

### Classification

Technical Classification	I/O device for bus system
Wieland Product Families	Flat and suitable for the flat cable - gesis EIB V

### General Data

Bus system EIB/KNX	Yes
Bus system LON	No
Bus system radio frequent	No
Bus connection included	Yes
Mounting method	Surface mounted (plaster)
Connection type	Plug-in connection
Degree of protection (IP)	IP20
Colour	Grey
RAL-number (akin)	7035

### Feed In

Operating voltage	230 V
Voltage type	AC
Bus input	KNX TP1
Different phases connectable	No

### Output

Voltage of switching output	230 V
-----------------------------	-------

# Product details

Voltage type of switching output	AC
Current of switching output	16 A
Max. number of switching contacts	2
Voltage of shutter output	230 V
Voltage type of shutter output	AC
Current of shutter output	8 A
Max. number of venetian-blind outputs	1
Manual control/hand actuation	No

## **Dimensions**

Width	254 mm
Height	112 mm
Depth	32 mm
Width in number of modular spacings	