

Product details

S/D-ACTUA.10V 2F GESIS EIB V-0/2SD SP

The gesis EIB V 2-fold switch-/dimming output has a 1-phase mains supply (3-pole GST18i3) connection. The flat device is for surface mounting and can be adapted directly to the flat cable. If a flat cable is used the adapters for mains and KNX are separate with a spacer which is added to the special KNX adapter. All electrical connections are pluggable.



Basic information

Article number	83.020.0213.4
EAN	4015573987791
Unit of measure	Piece
Packaging Quantity	1

Classification

Technical Classification	Dimming actuator for bus system
Wieland Product Families	Flat and suitable for the flat cable - gesis EIB V

General Data

Bus system EIB/KNX	Yes
Bus system LON	No
Bus system radio frequent	No
Bus connection included	Yes
Mounting method	Surface mounted (plaster)
Connection type	Plug-in connection
Degree of protection (IP)	IP20
Colour	Grey
RAL-number (akin)	7035
Modular expandability	No

Feed In

Operating voltage	230 V
Voltage type	AC
Bus input	KNX TP1
Different phases connectable	No
Additional power supply	No

Product details

Output

Number of outputs	2
Max. output power in VA	
Min. output power in VA	
Min. voltage	0 V
Max. Voltage	10 V
Frequency	0 Hz
Type of current	DC
Max. control current	50 mA
Type of load	
Manual control/hand actuation	No

Dimensions

Width	254 mm
Height	112 mm
Depth	32 mm
Width in number of modular spacings	