



Product details

ENOCLEAN GATEWAY GESIS EIB V-56/4 (RC)

The flat gesis EIB V 56-fold gateway for surface mounting and flat cable adaption is converting radio controlled EnOcean telegrams to KNX. Four switching outputs and a socket for external antenna are included. The 3-phase mains supply is done with a 5-pole GST18i 5 connector. All connections are pluggable.



Basic information

Article number	83.020.0220.2
EAN	4015573918443
Unit of measure	Piece
Packaging Quantity	1

Classification

Wieland Product Families	Flat and suitable for the flat cable
Wieland Product Families	Flat and suitable for the flat cable - gesis EIB V
Technical Classification	System interface/media gateway for bus system

General Data

Bus system EIB/KNX	Yes
Bus system LON	No
Bus system radio frequent	Yes
Mounting method	Surface mounted (plaster)
Connection type	Plug-in connection
Degree of protection (IP)	IP20
Colour	Grey
RAL-number (akin)	7035

Feed In

Operating voltage	400 V
Voltage type	AC
Bus input	KNX TP1
Different phases connectable	Yes

Input

Number of inputs	56
------------------	----



Product details

Input type	Radio control
------------	---------------

Output

Number of outputs

Maximum load

Mode

Voltage of switching output 230 V

Voltage type of switching output AC

Current of switching output 16 A

Manual control/hand actuation Yes

Max. number of switching contacts 4

Dimensions

Width 254 mm

Height 112 mm

Depth 32 mm

Width in number of modular spacings

Accessories

83.020.0503.0 ANTENNA GESIS RC A-A1SWL25